

ALBUS

IP66 ADJUSTABLE STREETLIGHT



Specifications

- For use on road, parks and environmental lighting
- Powder coat die-cast Aluminium case with tool-less detachable light engine
- Sosen driver (standard)
- 0-10V dimming, dim-to-off, DALI 2, D4i (option)
- Lumileds 3030 LED chips
- 10kV SPD standard
- Safety power cut-off switch
- Screwless connector blocks
- 3, 5 or 7 pin NEMA or Zhaga(option)
- Tempered glass IK09
- PC lens. Range of optics
- Side entry or post top mount
- Spigots available from 34mm to 76mm. $\pm 15^\circ$ angle adjustment
- 5 Year Warranty

Other wattage available : 20W, 40W, 50W, 80W, 150W, 180W

CODE	DIMENSIONS (L x W x D mm)	WATTAGE	LUMEN OUTPUT	LUMEN PER WATT	CRI	COLOUR TEMPERATURE
ALBUS-30W	500 x 220 x 90	30W	4200LM	140	70+	3000K-6000K
ALBUS-60W	500 x 220 x 90	60W	7300LM	121+	70+	3000K-6000K
ALBUS-100W	580 x 270 x 90	100W	12700LM	127	70+	3000K-6000K
ALBUS-120W	580 x 270 x 90	120W	15600LM	130	70+	3000K-6000K
ALBUS-200W	685 x 320 x 90	200W	27700LM	138+	70+	3000K-6000K