

CYLO PEARL MAGNETIC




Specifications


- White, black colour track mounted 48V low voltage spotlight with lighthead and arm in aluminium
- Versatile aiming angle tiltable vertically 0°-90° and rotatable horizontally 355°
- Easy to insert and remove from the track
- Option: Switchable or dimmable (1-10V, DALI, Touch-Dim, Casambi)
- IP20
- CRI 80/90
- 5 year Warranty




PEARL 1



PEARL 2 & 3



Optic Angle



CODE	DIMENSIONS Ø x H (mm)	WATTAGE	LUMEN OUTPUT	LUMEN PER WATT	CRI	COLOUR TEMPERATURE
CYLO PEARLM80-1	66 x 132 mm	6.1W	850	139+	80+	2700/3000/4000K
CYLO PEARLM90-1	66 x 132 mm	6.1W	729	119+	90+	2700/3000/4000K
CYLO PEARLM80-2	113.5 x 131 mm	2X6.1W	2X850	139+	80+	2700/3000/4000K
CYLO PEARLM90-2	113.5 x 131 mm	2X6.1W	2X729	119+	90+	2700/3000/4000K
CYLO PEARLM80-3	113.5 x 131 mm	3X6.1W	3X850	139+	80+	2700/3000/4000K
CYLO PEARLM90-3	113.5 x 131 mm	3X6.1W	3X729	119+	90+	2700/3000/4000K