

DUPONT

IP65 ADJUSTABLE STREETLIGHT



Specifications

- Ideal for use in urban outdoor leisure areas, pedestrian areas, parks, parking lots and many other uses
- Powder coat die-cast Aluminium case with tool-less opening driver compartment.
- Sosen driver (standard)
- 0-10V dimming, dim-to-off, DALI2, D4i (option)
- Lumileds 3030 LED chips
- 10kV SPD standard
- Screwless connector blocks
- 3, 5 or 7 pin NEMA or Zhaga(option)
- Tempered glass IK09
- PC lens. Range of optics
- IP65
- CRI>70
- 5 Year Warranty



CODE	DIMENSIONS (D x H mm)	WATTAGE	LUMEN OUTPUT	LUMEN PER WATT	CRI	COLOUR TEMPERATURE
DUPONT-20W	479 x 589 mm	20W	2800LM	140	70+	3000K-6000K
DUPONT-30W	479 x 589 mm	30W	4200LM	140	70+	3000K-6000K
DUPONT-40W	479 x 589 mm	40W	5600LM	140	70+	3000K-6000K
DUPONT-50W	479 x 589 mm	50W	7000LM	140	70+	3000K-6000K
DUPONT-60W	479 x 589 mm	60W	8400LM	140	70+	3000K-6000K
DUPONT-80W	479 x 589 mm	80W	11200LM	140	70+	3000K-6000K
DUPONT-100W	479 x 589 mm	100W	14000LM	140	70+	3000K-6000K
DUPONT-120W	479 x 589 mm	120W	16800LM	140	70+	3000K-6000K