

LINA105 RECESSED




Specifications

- White, grey, black electrostatic powder coated aluminium extrusion housing
- Opal PC diffuser
- Option: Prismatic-Microprismatic diffuser
- Other lengths and wattages available on request
- Option: Switchable or dimmable (1-10V, DALI, Touch-Dim, Casambi)
- SDCM ≤ 3 (3-step Mac Adam)
- CRI 80
- 5 Year Warranty



W: 105mm - D: 85mm - H: 55mm

L: 1140mm / 1700mm / 2000mm / 3100mm



cd/klm
— C0 - C180 — C90 - C270 — %100

CODE	DIMENSIONS LxWxH mm	CUTOUT	WATTAGE	LUMEN OUTPUT	LUMEN PER WATT	CRI	COLOUR TEMPERATURE
LINA105 - REC - 44W	1140x105x55 mm	85*1120	44W	4800LM	109	80	3000K-6500K
LINA105 - REC - 66W	1700x105x55 mm	85*1680	66W	7200LM	109	80	3000K-6500K
LINA105 - REC - 80W	2000x105x55 mm	85*1980	80W	8400LM	105	80	3000K-6500K
LINA105 - REC - 124W	3100x105x55 mm	85*3080	124W	13200LM	106	80	3000K-6500K