

LINA55 - RECESSED



Specifications

- White, grey, black electrostatic powder coated aluminium extrusion housing
- Opal PC diffuser
- Option: Prismatic-Microprismatic diffuser
- Other lengths and wattages available on request
- Option: Switchable or dimmable (1-10V, DALI, Touch-Dim, Casambi)
- SDCM ≤ 3 (3-step Mac Adam)
- CRI 80
- 5 Year Warranty



CODE	DIMENSIONS LxWxH mm	WATTAGE	LUMEN OUTPUT	LUMEN PER WATT	CRI	COLOUR TEMPERATURE
LINA55-REC-14W-600	600x55x40 mm	14W	1610LM	115	80	3000K-6500K
LINA55-REC-18W-600	600x55x40 mm	18W	2070LM	115	80	3000K-6500K
LINA55-REC-20W-900	900x55x40 mm	20W	2300LM	115	80	3000K-6500K
LINA55-REC-27W-900	900x55x40 mm	27W	3105LM	115	80	3000K-6500K
LINA55-REC-27W-1200	1200x55x40 mm	27W	3105LM	115	80	3000K-6500K
LINA55-REC-36W-1200	1200x55x40 mm	36W	4140LM	115	80	3000K-6500K
LINA55-REC-33W-1500	1500x55x40 mm	33W	3795LM	115	80	3000K-6500K
LINA55-REC-45W-1500	1500x55x40 mm	45W	5175LM	115	80	3000K-6500K
LINA55-REC-53W-2400	2400x55x40 mm	53W	6095LM	115	80	3000K-6500K
LINA55-REC-72W-2400	2400x55x40 mm	72W	8280LM	115	80	3000K-6500K