

## LINA55 - SUSPENDED



### Specifications

- White, grey, black electrostatic powder coated aluminium extrusion housing
- Opal PC diffuser
- Option: Prismatic-Microprismatic diffuser
- Other lengths and wattages available on request
- Option: Switchable or dimmable (1-10V, DALI, Touch-Dim, Casambi)
- SDCM  $\leq 3$  (3-step Mac Adam)
- CRI 80
- 5 Year Warranty

| CODE                | DIMENSIONS<br>LxWxH mm | WATTAGE | LUMEN<br>OUTPUT | LUMEN PER<br>WATT | CRI | COLOUR<br>TEMPERATURE |
|---------------------|------------------------|---------|-----------------|-------------------|-----|-----------------------|
| LINA55-SUS-14W-600  | 600x55x679mm           | 14W     | 1610LM          | 115               | 80  | 3000K-6500K           |
| LINA55-SUS-18W-600  | 600x55x79 mm           | 18W     | 2070LM          | 115               | 80  | 3000K-6500K           |
| LINA55-SUS-20W-900  | 900x55x79 mm           | 20W     | 2300LM          | 115               | 80  | 3000K-6500K           |
| LINA55-SUS-27W-900  | 900x55x79 mm           | 27W     | 3105LM          | 115               | 80  | 3000K-6500K           |
| LINA55-SUS-27W-1200 | 1200x55x79 mm          | 27W     | 3105LM          | 115               | 80  | 3000K-6500K           |
| LINA55-SUS-36W-1200 | 1200x55x79 mm          | 36W     | 4140LM          | 115               | 80  | 3000K-6500K           |
| LINA55-SUS-33W-1500 | 1500x55x79 mm          | 33W     | 3795LM          | 115               | 80  | 3000K-6500K           |
| LINA55-SUS-45W-1500 | 1500x55x79 mm          | 45W     | 5175LM          | 115               | 80  | 3000K-6500K           |
| LINA55-SUS-53W-2400 | 2400x55x79 mm          | 53W     | 6095LM          | 115               | 80  | 3000K-6500K           |
| LINA55-SUS-72W-2400 | 2400x55x79 mm          | 72W     | 8280LM          | 115               | 80  | 3000K-6500K           |