

LINA65 - RECESSED



Specifications

- White, grey, black electrostatic powder coated aluminium extrusion housing
- Opal PC diffuser
- Option: Prismatic-Microprismatic diffuser
- Other lengths and wattages available on request
- Option: Switchable or dimmable (1-10V, DALI, Touch-Dim, Casambi)
- SDCM ≤ 3 (3-step Mac Adam)
- CRI 80
- 5 Year Warranty

CODE	DIMENSIONS LxWxH mm	WATTAGE	LUMEN OUTPUT	LUMEN PER WATT	CRI	COLOUR TEMPERATURE
LINA65-REC-26W	1140x65x43 mm	26W	2600LM	100	80	3000K-6500K
LINA65-REC-40W	1140x65x43 mm	40W	4800LM	120	80	3000K-6500K
LINA65-REC-46W	2000x65x43 mm	46W	4550LM	98+	80	3000K-6500K
LINA65-REC-60W	1700x65x43 mm	60W	7200LM	120	80	3000K-6500K
LINA65-REC-73W	3100x65x43 mm	73W	6935LM	95+	80	3000K-6500K
LINA65-REC-80W	2000x65x43 mm	80W	9600LM	120	80	3000K-6500K
LINA65-REC-110W	3100x65x43 mm	110W	13250LM	120	80	3000K-6500K