

LINA70 - RECESSED



Specifications

- White, grey, black color electrostatic powder coated aluminium extrusion housing
- SMD LED light source
- Lighting grade PC opal diffuser
- Microprismatic diffuser options for extra glare control
- Switchable or dimmable (1-10V, DALI, Touch-Dim, Casambi)
- Option: 3 Hours emergency kit
- L80B10 - 60.000 hours
- SDCM ≤ 3 (3-step Mac Adam)
- CRI 80
- 5 Year Warranty



CODE	DIMENSIONS LxWxH mm	WATTAGE	LUMEN OUTPUT	LUMEN PER WATT	CRI	COLOUR TEMPERATURE
LINA70-REC-18W	630x70x40 mm	18W	2070LM	115	80	3000K-6500K
LINA70-REC-20W	930x70x40 mm	20W	2300LM	115	80	3000K-6500K
LINA70-REC-27W	1230x70x40 mm	27W	3105LM	115	80	3000K-6500K
LINA70-REC-33W	1530x70x40 mm	33W	3795LM	115	80	3000K-6500K
LINA70-REC-45W	1530x70x40 mm	45W	5175LM	115	80	3000K-6500K
LINA70-REC-53W	2430x65x43 mm	53W	6095LM	115	80	3000K-6500K
LINA70-REC-72W	2430x65x43 mm	72W	8280LM	115	80	3000K-6500K